


螺旋锥齿轮 Gear

锥齿轮模数为0.5-6的齿轮 modulus of bevel gear for 0.5-6 gear

弧形锥齿轮,螺旋角35°,压力角20°Curved bevel gear, Helix angle 35°pressure angle 20°



标记示例:

1M-20-12-L

左旋 L

内孔 Bore

齿数 Number of teeth

模数 Module

型号 Code	比数	模数 Module	齿数 Z	螺旋 方向	孔径 AH7	轮廓径 B	分度圆 C	齿顶圆 D	安装 距离E	全长 F	齿顶距离 G	轮毂长 H	孔长 I	齿宽 J	键槽 宽x深	侧隙 (mm)
M2-30	1.5	M2	30	R	20 22	40	60	61.36	40	26.80	21.02	14.00	23.0	11	6x2.8 6x2.8	0.06~0.16
M2-20	1.5	M2	20	L	15 18	35	40	43.49	45	24.96	16.16	13.33	23.0	11	5x2.3 6x2.8	0.06~0.16
M2.5-30	1.5	M2.5	30	R	22 25	48	75	76.74	50	33.60	26.31	18.00	30.0	14	6x2.8 8x3.3	0.07~0.17
M2.5-20	1.5	M2.5	20	L	18 20	43	50	54.43	55	30.08	18.98	15.17	28.0	14	6x2.8 6x2.8	0.07~0.17
M3-30	1.5	M3	30	R	25 30	60	90	92.21	60	40.34	31.66	21.00	36.0	17	8x3.3 8x3.3	0.08~0.18
M3-20	1.5	M3	20	L	22 25	53	60	65.58	65	35.17	21.86	17.00	32.5	17	6x2.8 8x3.3	0.08~0.18
M4-30	1.5	M4	30	R	35 40	75	120	122.91	70	43.99	32.18	21.00	39.0	23	10x3.3 12x3.3	0.12~0.27
M4-20	1.5	M4	20	L	30 35	70	80	87.34	85	45.53	27.45	21.67	42.0	23	8x3.3 10x3.3	0.12~0.27
M5-30	1.5	M5	30	R	35	90	150	153.67	90	58.08	42.75	24.00	50.0	30	22x5.4	0.14~0.34
M5-20	1.5	M5	20	L	35 40	80	100	109.20	110	61.62	38.07	28.33	56.0	30	10x3.3 12x3.3	0.14~0.34
M2-40	2	M2	40	R	20 22	45	80	81.06	45	31.83	26.06	18.00	29.0	14	6x2.8 6x2.8	0.06~0.16
M2-20	2	M2	20	L	15 18	35	40	44.20	55	28.16	16.05	13.75	27.0	14	5x2.3 6x2.8	0.06~0.16
M2.5-40	2	M2.5	40	R	25 28	55	100	101.29	50	33.35	26.33	16.00	30.0	17	8x3.3 8x3.3	0.07~0.17
M2.5-20	2	M2.5	20	L	20 22	43	50	55.12	65	30.01	16.28	13.25	29.0	17	6x2.8 6x2.8	0.07~0.17
M3-40	2	M3	40	R	30 35	65	120	121.57	60	39.81	31.57	21.00	35.0	20	8x3.3 10x3.3	0.08~0.18
M3-20	2	M3	20	L	22 25	53	60	66.03	80	38.90	21.51	18.25	36.5	20	6x2.8 8x3.3	0.08~0.18
M4-40	2	M4	40	R	30	70	160	162.07	80	53.69	42.07	28.00	45.0	28	8x3.3	0.12~0.27
M4-20	2	M4	20	L	30 35	60	80	88.50	120	66.24	42.12	35.00	62.0	28	8x3.3 10x3.3	0.12~0.27
M5-40	2	M5	40	R	40	100	200	202.54	90	55.02	42.54	26.00	50.0	30	12x3.3	0.14~0.34
M5-20	2	M5	20	L	40 45	80	100	110.45	140	68.48	42.61	35.00	63.0	30	12x3.3 14x3.8	0.14~0.34

精度等级: (JIS4级)DIN8e27

材料: 20CrMnTi

齿型: 螺旋伞齿轮

齿面处理: 精铣或刨削

硬度处理: 45~55度HRC

螺旋角: 35°

压力角: 20度

注: 所有尺寸均为毫米

Precision Grade: (JIS Grade 4)DIN 8e27

Material: 20CrMnTi

Type: Spiral bevel gear

Treatment of Teeth: Milled

Hardness: 45~55 degree HRC

Helix Angle: 35°

Pressure Angle: 20 degree