


胀紧联结套 Keyless Locking Devices

胀紧联结套-R01型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例:

类似JB/T 7934 Z2型胀套

R01-19-47

外径 Dia

内径 Bore

型号 Code

尺寸 Dimensions					传递的 轴向力 Axial Force	传递扭矩 Torque	接触面压强 Contact Pressure		DIN912-12.9级锁紧螺钉 Locking Screws DIN912-12.9			重量 Weight
Φd	ΦD	L1	L2	L			轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque	
mm	mm	mm	mm	mm	KN	Nm	P N/mm ²	P1 N/mm ²	Qty.	Size	TS Nm	Kgs
19	47	17	20	26	31	298	286	116	8	M6x18	14.9	0.20
20	47	17	20	26	31	313	272	116	8	M6x18	14.9	0.22
22	47	17	20	26	31	345	247	116	8	M6x18	14.9	0.23
24	50	17	20	26	35	424	255	123	9	M6x18	14.9	0.23
25	50	17	20	26	35	441	245	123	9	M6x18	14.9	0.23
28	55	17	20	26	39	549	243	124	10	M6x18	14.9	0.27
30	55	17	20	26	39	588	227	124	10	M6x18	14.9	0.26
32	60	17	20	26	47	752	255	136	12	M6x18	14.9	0.28
35	60	17	20	26	47	822	233	136	12	M6x18	14.9	0.30
38	63	17	20	26	47	830	242	140	14	M6x18	14.9	0.31
38	65	17	20	26	55	1042	250	146	14	M6x18	14.9	0.33
40	65	17	20	26	55	1097	238	146	14	M6x18	14.9	0.32
42	75	20	24	32	83	1740	291	163	12	M8x22	35.0	0.57
45	75	20	24	32	83	1864	271	163	12	M8x22	35.0	0.55
48	80	20	24	32	83	1988	254	153	12	M8x22	35.0	0.60
50	80	20	24	32	83	2071	244	153	12	M8x22	35.0	0.56
55	85	20	24	32	97	2658	259	168	14	M8x22	35.0	0.65
60	90	20	24	32	97	2900	238	158	14	M8x22	35.0	0.66
65	95	20	24	32	110	3587	250	171	16	M8x22	35.0	0.72
70	110	24	28	38	153	5345	268	171	14	M10x25	69.0	1.27
75	115	24	28	38	153	5727	250	163	14	M10x25	69.0	1.33
80	120	24	28	38	153	6108	235	156	14	M10x25	69.0	1.35
85	125	24	28	38	175	7417	252	172	16	M10x25	69.0	1.45
90	130	24	28	38	175	7854	238	165	16	M10x25	69.0	1.55
95	135	24	28	38	196	9326	254	179	18	M10x25	69.0	1.65
100	145	26	33	45	227	11362	258	178	14	M12x30	123.3	2.20
110	155	26	33	45	227	12498	234	166	14	M12x30	123.3	2.40
120	165	26	33	45	260	15578	245	178	16	M12x30	123.3	2.60
130	180	34	38	50	325	21095	217	156	20	M12x35	123.3	3.60
140	190	34	38	50	357	24993	221	163	22	M12x35	123.3	3.80
150	200	34	38	50	390	29217	225	169	24	M12x35	123.3	4.10
160	210	34	38	50	422	33756	229	174	26	M12x35	123.3	4.50
170	225	38	44	58	465	39483	212	160	22	M14x40	187.0	5.90
180	235	38	44	58	507	45606	218	167	24	M14x40	187.0	6.10
190	250	46	52	66	591	56163	199	152	28	M14x45	187.0	8.50
200	260	46	52	66	633	63342	203	156	30	M14x45	187.0	9.00
220	285	50	56	72	745	81960	200	154	26	M16x50	290.0	11.00
240	305	50	56	72	860	103162	211	166	30	M16x50	290.0	12.40
260	325	50	56	72	974	126669	221	177	34	M16x50	290.0	19.30
280	355	60	66	84	1124	157339	197	156	32	M18x60	400.0	21.10
300	375	60	66	84	1264	189653	207	166	36	M18x60	400.0	21.50
320	405	72	78	98	1651	264108	211	167	36	M20x70	580.0	29.80