


胀紧联结套 Keyless Locking Devices



胀紧联结套-R02型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例:

类似JB/T 7934 Z11型胀套

R02-30-41

外径 Dia

内径 Bore

型号 Code

尺寸 Dimensions								传递的 轴向力 Axial Force	传递扭矩 Torque	接触面压强 Contact Pressure		DIN912-12.9级锁紧螺钉 Locking Screws DIN912-12.9			重量 Weight
										轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque	
Φd mm	ΦD mm	L1 mm	L2 mm	L3 mm	L mm	ΦD2	ΦD1	Ft KN	Mt Nm	P N/mm ²	P1 N/mm ²	Qty.	Size	TS Nm	Kgs
6	14	10	19	21	24	25	21	4	12	185	80	3	M3x10	2.0	0.05
8	15	12	21	24	28	32	28	10	39	299	159	4	M4x10	5.2	0.07
9	16	14	23	27	31	32	28	10	44	227	128	4	M4x12	5.2	0.07
10	16	14	23	27	31	32	28	10	49	205	128	4	M4x12	5.2	0.07
11	18	14	23	27	31	34	30	10	53	186	114	4	M4x12	5.2	0.07
12	18	14	23	27	31	34	30	10	58	171	114	4	M4x12	5.2	0.08
14	23	14	23	27	31	39	35	10	68	146	89	4	M4x12	5.2	0.11
15	24	16	29	36	42	45	40	16	120	196	123	4	M6x18	17.0	0.22
16	24	16	29	36	42	45	40	16	128	184	123	4	M6x18	17.0	0.22
18	26	18	31	38	44	47	42	21	191	194	134	4	M6x18	17.0	0.23
19	27	18	31	38	44	48	43	21	202	183	129	4	M6x18	17.0	0.25
20	28	18	31	38	44	49	44	21	213	174	124	4	M6x18	17.0	0.26
22	32	25	38	45	51	54	48	21	234	114	78	4	M6x18	17.0	0.35
24	34	25	38	45	51	56	50	21	255	105	74	4	M6x18	17.0	0.36
25	34	25	38	45	51	56	50	21	266	100	74	4	M6x18	17.0	0.34
28	39	25	38	45	51	61	55	27	373	112	81	5	M6x18	17.0	0.42
30	41	25	38	45	51	63	57	32	480	126	92	6	M6x18	17.0	0.43
32	43	30	43	50	56	65	59	32	511	98	73	6	M6x18	17.0	0.49
35	47	30	43	50	56	69	63	43	747	120	89	8	M6x18	17.0	0.55
38	50	30	43	50	56	72	66	43	811	110	84	8	M6x18	17.0	0.62
40	53	32	45	52	58	75	69	48	959	110	83	9	M6x18	17.0	0.64
42	55	32	45	52	58	77	71	48	1007	105	80	9	M6x18	17.0	0.85
45	59	40	56	64	72	85	79	79	1781	130	99	8	M8x22	42.0	1.05
48	62	40	56	64	72	88	82	79	1900	122	94	8	M8x22	42.0	1.13
50	65	50	66	74	82	92	85	99	2473	117	90	10	M8x22	42.0	1.26
55	71	50	66	74	82	98	91	99	2721	106	82	10	M8x22	42.0	1.53
60	77	50	66	74	82	104	97	99	2968	97	76	10	M8x22	42.0	1.66
65	84	50	66	74	82	111	104	99	3215	90	69	10	M8x22	42.0	1.90
70	90	60	80	91	101	122	115	127	4430	89	69	8	M10x25	84.0	3.00
75	95	60	80	91	101	126	119	142	5338	93	74	9	M10x25	84.0	3.10
80	100	65	85	96	106	131	124	190	7595	108	86	12	M10x25	84.0	3.30
85	106	65	85	96	106	137	130	190	8069	101	81	12	M10x25	84.0	3.60
90	112	65	85	96	106	143	136	222	9968	112	90	14	M10x25	84.0	4.00
95	120	65	85	96	106	153	144	222	10522	106	84	14	M10x25	84.0	4.70
100	125	65	89	102	114	162	153	273	13651	124	99	12	M12x30	145.0	5.20
110	140	70	94	107	119	177	168	273	15016	105	82	12	M12x30	145.0	8.70
120	155	90	114	127	139	195	185	364	21844	99	77	16	M12x30	145.0	10.6
130	165	90	114	127	139	205	195	364	23664	92	72	16	M12x30	145.0	11.3
140	175	90	114	127	139	215	205	364	25485	85	68	16	M12x30	145.0	12.6
150	185	90	114	127	139	225	215	364	27305	80	64	16	M12x30	145.0	14.8