


胀紧联结套 Keyless Locking Devices



胀紧联结套-R04型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例:

类似 JB/T 7934 Z3 加长型胀套

R04-19-47

外径 Dia

内径 Bore

型号 Code

尺寸 Dimensions						传递的轴 向力 Axial Force	传递 扭矩 Torque	接触面压强 Contact Pressure		DIN912-12.9级锁紧螺钉 Locking Screws DIN912-12.9			重量 Weight
								轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque	
Φd mm	ΦD mm	L1 mm	L2 mm	L3 mm	L mm	Ft KN	Mt Nm	P N/mm ²	P1 N/mm ²	Qty.	Size	TS Nm	Kgs
19	47	26	31	39	45	32	307	193	78	4	M6x25	17	0.37
20	47	26	31	39	45	32	323	183	78	4	M6x25	17	0.37
22	47	26	31	39	45	32	355	166	78	4	M6x25	17	0.35
24	50	26	31	39	45	48	582	229	110	6	M6x25	17	0.40
25	50	26	31	39	45	48	606	220	110	6	M6x25	17	0.38
28	55	26	31	39	45	48	679	196	100	6	M6x25	17	0.45
30	55	26	31	39	45	48	727	183	100	6	M6x25	17	0.43
32	60	26	31	39	45	65	1033	229	122	8	M6x25	17	0.53
35	60	26	31	39	45	65	1130	209	122	8	M6x25	17	0.50
38	65	26	31	39	45	65	1227	193	113	8	M6x25	17	0.60
40	65	26	31	39	45	65	1292	183	113	8	M6x25	17	0.56
42	75	30	36	47	55	87	1835	204	115	6	M8x30	41	0.95
45	75	30	36	47	55	87	1966	191	115	6	M8x30	41	0.92
48	80	30	36	47	55	87	2097	179	107	6	M8x30	41	1.10
50	80	30	36	47	55	87	2184	172	107	6	M8x30	41	1.00
55	85	30	36	47	55	116	3202	208	135	8	M8x30	41	1.10
60	90	30	36	47	55	116	3493	191	127	8	M8x30	41	1.16
65	95	30	36	47	55	116	3784	176	120	8	M8x30	41	1.20
70	110	40	46	57	67	189	6607	199	127	8	M10x35	83	2.30
75	115	40	46	62	72	189	7079	186	121	8	M10x35	83	2.50
80	120	40	46	62	72	189	7551	174	116	8	M10x35	83	2.70
85	125	40	46	62	72	236	10029	205	139	10	M10x35	83	2.90
90	130	40	46	62	72	236	10619	193	134	10	M10x35	83	3.20
95	135	40	46	62	72	236	11209	183	129	10	M10x35	83	3.50
100	145	46	52	77	89	275	13738	176	121	8	M12x45	145	4.00
110	155	46	52	77	89	275	15111	160	114	8	M12x45	145	4.30
120	165	46	52	77	89	343	20606	183	133	10	M12x45	145	4.40
130	180	46	52	77	89	412	26788	203	147	12	M12x45	145	5.70
140	190	51	59	84	98	373	26142	154	114	8	M14x45	230	6.70
150	200	51	59	84	98	467	35016	180	135	10	M14x45	230	7.00
160	210	51	59	84	98	467	37351	169	129	10	M14x45	230	7.00
170	225	51	59	84	98	560	47617	191	144	12	M14x45	230	8.50
180	235	51	59	84	98	560	50418	180	138	12	M14x45	230	9.00