


胀紧联结套 Keyless Locking Devices

胀紧联结套-R13型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例: 类似 JB/T 7934 Z14 胀套

R13-14-25

外径 Dia

内径 Bore

型号 Code

标准胀套不含螺栓,如需要螺栓请特别提出

The standard locking device doesn't include bolts. Please contact us if you need

尺寸 Dimensions								传递的轴向力 Transmitted Axial Force	传递扭矩 Transmitted Torque	接触面压强 Contact Pressure		DIN912锁紧螺钉12.9级(1) DIN912 Locking Screw12.9(1)		
										轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque
Φd mm	ΦD mm	ΦD1 mm	ΦDT mm	L mm	L1 mm	L2 mm	L3 mm	Ft KN	Mt Nm	P N/mm ²	P1 N/mm ²	Qty.	Size	TS Nm
14	25	42	33	16	20	26	30	9	64	109	0	4	M4	2.9
16									73	96				
18									82	85				
19									87	81				
20	30	50	39	16	20	26	31	15	152	127	65	4	M5	6
22									167	116				
24									182	106				
25									190	102				
28	36	55	45	16	20	26	31	15	213	91	57	4	M5	6
30									228	85				
32									243	80				
35	42	62	51	16	20	28	33	5	266	73	50	4	M5	6
36									274	71				
38									400	93	65	4	M6	10
40	48	70	58	16	20	28	34	21	421	88				
42									442	84				
45	55	82	67	20	25	35	43	40	890	118	79	4	M8	25
48									949	110				
50	62	89	74	20	25	35	43	40	989	106	72	4	M8	25
55									1088	96				
60									1187	88	63	4	M8	25
65	72	99	84	20	25	35	43	40	1286	82				