




胀紧联结套 Keyless Locking Devices

胀紧联结套-R17型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例: 类似 JB/T 7934 Z19A 型胀套

R17-14-25

外径 Dia

内径 Bore

型号 Code

尺寸 Dimensions					传递的 轴向力 Axial Force	传递 扭矩 Torque	接触面压强 Contact Pressure		Slotted out (开槽螺母) Slotted Nut Thread Din1804		
							轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque
d	D	D1	H	h1	Ft	Mt	P	P1	Qty.	Size	TS
mm	mm	mm	mm	mm	KN	Nm	N/mm ²	N/mm ²			Nm
14	25	32	16.5	6.5	7	52	241	135	1	M20x1	95
15	25	32	16.5	6.5	7	56	225	135	1	M20x1	95
16	25	32	16.5	6.5	7	60	211	135	1	M20x1	95
18	30	38	18.0	6.5	10	91	256	154	1	M25x1.5	160
19	30	38	18.0	6.5	10	96	242	154	1	M25x1.5	160
20	30	38	18.0	6.5	10	102	230	154	1	M25x1.5	160
24	35	45	18.0	6.5	12	139	218	150	1	M30x1.5	220
25	35	45	18.0	6.5	12	144	210	150	1	M30x1.5	220
28	40	52	19.5	7.0	15	215	248	174	1	M35x1.5	340
30	40	52	19.5	7.0	15	230	188	141	1	M35x1.5	340
35	45	58	21.5	8.0	19	331	199	155	1	M40x1.5	480
40	50	65	24.5	10.0	24	477	176	141	1	M45x1.5	680
40	52	65	24.5	10.0	27	480	176	141	1	M45x1.5	680
45	57	70	25.5	10.0	27	617	180	147	1	M50x1.5	870
48	62	75	25.5	10.0	28	669	171	137	1	M55x2	970
50	62	75	25.7	10.0	28	697	164	137	1	M55x2	970
55	68	80	27.5	12.0	29	796	129	109	1	M60x2	1100
60	73	85	28.5	12.0	32	946	129	111	1	M65x2	1300