




胀紧联结套 Keyless Locking Devices

胀紧联结套-R18型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例:

类似 JB/T 7934 Za型胀套

R18- 10 - 20

外径 Dia

内径 Bore

型号 Code

尺寸 Dimensions				传递的 轴向力 Axial Force	传递 扭矩 Torque	接触面压强 Contact Pressure		DIN912-12.9级锁紧螺钉 Locking Screws DIN912-12.9		
						轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque
d mm	D mm	L1 mm	L mm	Ft KN	Mt Nm	P N/mm ²	P1 N/mm ²	Qty.	Size	TS Nm
10	20	13	15.5	3.8	19	89	45	4	M2.5x12	1.2
11	22	13	15.5	3.8	21	81	41	4	M2.5x12	1.2
12	22	13	15.5	3.8	23	75	41	4	M2.5x12	1.2
14	26	17	20	5.5	39	71	38	4	M3x16	2.1
15	28	17	20	5.5	42	66	35	4	M3x16	2.1
16	32	17	21	9.6	77	107	54	4	M4x16	4.9
17	35	21	25	9.6	82	81	40	4	M4x20	4.9
18	35	21	25	9.6	87	77	40	4	M4x20	4.9
19	35	21	25	9.6	91	73	40	4	M4x20	4.9
20	38	21	26	15.7	157	113	60	4	M5x20	10.0
22	40	21	26	15.7	173	103	57	4	M5x20	10.0
24	47	26	32	22.3	268	110	56	4	M6x24	17.0
25	47	26	32	22.3	279	105	56	4	M6x24	17.0
28	50	26	32	33.5	468	141	79	6	M6x24	17.0
30	55	26	32	33.5	502	132	72	6	M6x24	17.0
32	55	26	32	33.5	535	123	72	6	M6x24	17.0
35	60	31	37	44.6	781	125	73	8	M6x28	17.0
38	65	31	37	44.6	848	115	67	8	M6x28	17.0
40	65	31	37	44.6	892	110	67	8	M6x28	17.0
42	75	36	44	60.6	1272	122	68	6	M8x34	41.0
45	75	36	44	60.6	1363	113	68	6	M8x34	41.0
48	80	36	44	80.8	1938	142	85	8	M8x34	41.0
50	80	36	44	80.8	2019	136	85	8	M8x34	41.0