




胀紧联结套 Keyless Locking Devices

胀紧联结套- R19型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例:

R19-25-50

外径 Dia

内径 Bore

型号 Code

类似 JB/T 7934 Z12A 型胀套

尺寸 Dimensions					传递的 轴向力 Axial Force	传递 扭矩 Torque	接触面压强 Contact Pressure		DIN912-12.9级锁紧螺钉 Locking Screws DIN912-12.9			重量 Weight
							轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque	
d	D	H	H1	H2	Ft	Mt	P	P1	Qty.	Size	TS	Kgs
mm	mm	mm	mm	mm	KN	Nm	N/mm ²	N/mm ²			Nm	
25	50	46	40	32	64	799	314	107	6	M6x35	17	0.35
28	55	46	40	32	64	895	281	107	6	M6x35	17	0.42
30	55	46	40	32	64	959	262	107	6	M6x35	17	0.40
35	60	60	54	44	75	1306	185	83	7	M6x45	17	0.60
38	65	62	54	44	135	2567	308	121	7	M8x50	41	1.15
40	65	51	45	39	135	2702	293	121	7	M8x50	41	1.10
40	75	62	54	44	135	2780	284	121	7	M8x50	41	1.35
42	75	62	54	44	135	2837	279	121	7	M8x50	41	1.25
45	75	62	54	44	135	3040	260	121	7	M8x50	41	1.15
48	80	72	64	56	154	3707	216	102	8	M8x55	41	1.30
50	80	72	64	56	154	3861	207	102	8	M8x55	41	1.26
55	85	72	64	56	174	4779	212	108	9	M8x55	41	1.36
60	90	72	64	56	193	5793	216	113	10	M8x55	41	1.46
65	95	72	64	56	193	6276	199	107	10	M8x55	41	1.55
70	110	88	78	70	313	10951	235	120	10	M10x60	83	2.90
75	115	88	78	70	313	11733	220	115	10	M10x60	83	3.00
80	120	88	78	70	344	13768	227	121	11	M10x60	83	3.30
85	125	88	78	70	376	15959	233	127	12	M10x60	83	3.40
90	130	88	78	70	376	16898	220	122	12	M10x60	83	3.50
95	135	88	78	70	376	17837	208	117	12	M10x60	83	3.70
100	145	112	100	90	501	25029	211	113	11	M12x80	145	5.50
110	155	112	100	90	546	30039	209	115	12	M12x80	145	6.00
120	165	112	100	90	637	38226	224	127	14	M12x80	145	6.40
130	180	130	116	104	743	48270	201	117	12	M14x90	230	10.00
140	190	130	116	104	866	60654	217	129	14	M14x90	230	10.00
150	200	130	116	104	928	69628	217	132	15	M14x90	230	10.30
160	210	130	116	104	990	79220	217	134	16	M14x90	230	12.40
170	225	164	148	134	1186	100851	206	116	14	M16x110	360	15.70
180	235	164	148	134	1271	114414	208	119	15	M16x110	360	17.60
190	250	164	148	134	1356	128814	210	119	16	M16x110	360	19.60
200	260	164	148	134	1356	135594	200	115	16	M16x110	360	21.50
220	285	164	148	134	1526	167805	204	118	18	M16x110	360	33.00