




胀紧联结套 Keyless Locking Devices

胀紧联结套-R21型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例: 类似 JB/T 7934 Z19B 型胀套

R21-15-25

外径 Dia

内径 Bore

型号 Code

尺寸 Dimensions					传递的 轴向力 Axial Force	传递 扭矩 Torque	接触面压强 Contact Pressure		Slotted out (开槽螺母) Slotted Nut Thread Din1804		
							轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque
d	D	D1	H	h1	Ft	Mt	P	P1	Qty.	Size	TS
mm	mm	mm	mm	mm	KN	Nm	N/mm ²	N/mm ²			Nm
15	25	32	31	20	9	77	91	55	1	M20x1	95
18	30	38	33	21	13	125	98	59	1	M25x1.5	160
19	30	38	33	21	13	132	93	59	1	M25x1.5	160
20	30	38	33	21	13	139	88	59	1	M25x1.5	160
24	35	45	38	25	15	202	74	51	1	M30x1.5	220
25	35	45	38	25	15	210	71	51	1	M30x1.5	220
28	40	52	44	28	20	312	76	53	1	M35x1.5	340
30	40	52	44	28	20	335	71	53	1	M35x1.5	340
35	45	58	45	28	25	483	75	58	1	M40x1.5	480
40	50	65	46	28	31	696	82	66	1	M45x1.5	680
45	55	70	47	28	36	902	84	69	1	M50x1.5	870
50	60	75	47	28	37	1014	77	64	1	M55x2	970
55	65	80	48	28	38	1158	73	61	1	M60x2	1100
60	70	85	50	28	41	1379	73	62	1	M65x2	1300