




胀紧联结套 Keyless Locking Devices

胀紧联结套-R22型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

标记示例:

R22-15-45

— 外径 Dia

— 内径 Bore

— 型号 Code

类似 JB/T 7934 Z17 型胀套

尺寸 Dimensions						传递的 轴向力 Axial Force	传递 扭矩 Torque	接触面压强 Contact Pressure	DIN912-12.9级锁紧螺钉 Locking Screws DIN912-12.9		
								轴 Shaft	数量	规格	锁紧扭矩 Tightening Torque
d	D	L	L1	L2	L3	Ft	Mt	P	Qty.	Size	TS
mm	mm	mm	mm	mm	mm	KN	Nm	N/mm ²			Nm
15	45	56	50	16.0	44	21	158	188	4	M6x45	17
16	50	56	50	16.0	44	21	168	176	4	M6x45	17
17	50	56	50	16.0	44	21	179	166	4	M6x45	17
18	50	56	50	16.0	44	21	190	157	4	M6x45	17
19	50	56	50	16.0	44	21	200	149	4	M6x45	17
20	50	56	50	16.0	44	21	211	141	4	M6x45	17
24	55	66	60	18.5	54	32	378	144	6	M6x55	17
25	55	66	60	18.5	54	32	394	138	6	M6x55	17
28	60	66	60	18.5	54	32	442	123	6	M6x55	17
30	60	66	60	18.5	54	32	473	115	6	M6x55	17
32	63	66	60	18.5	54	32	505	108	6	M6x55	17
35	75	83	75	22.0	67	39	682	98	4	M8x70	42
38	75	83	75	22.0	67	39	741	90	4	M8x70	42
40	75	83	75	22.0	67	39	780	86	4	M8x70	42
42	78	83	75	22.0	67	39	819	82	4	M8x70	42
45	85	93	85	24.5	76	59	1317	101	6	M8x80	42
48	90	93	85	24.5	76	59	1405	95	6	M8x80	42
50	90	93	85	24.5	76	59	1463	91	6	M8x80	42
55	94	93	85	24.5	76	78	2147	110	8	M8x80	42
60	100	93	85	24.5	76	78	2343	101	8	M8x80	42
65	105	93	85	24.5	76	78	2538	93	8	M8x80	42
70	115	110	100	29.0	90	123	4321	116	8	M10x95	83