




胀紧联结套 Keyless Locking Devices

胀紧联结套-R37型



推荐安装尺寸: The dimension to fix (suggestion):

轴: h8 Shaft: h8

毂: H8 Hub: H8

标记示例:

R37-100-145

类似 JB/T 7934 Z5 型胀套

外径 Dia

内径 Bore

型号 Code

尺寸 Dimensions					传递的 轴向力 Axial Force	传递 扭矩 Torque	接触面压强 Contact Pressure		DIN912-12.9级锁紧螺钉 Locking Screws DIN912-12.9		
							轴 Shaft	毂 Hub	数量	规格	锁紧扭矩 Tightening Torque
d mm	D mm	L mm	L1 mm	L2 mm	Ft KN	Mt Nm	P N/mm ²	P1 N/mm ²	Qty.	Size	TS Nm
100	145	60	65	77	288	14400	192	132	10	M12x55	145
110	155	60	65	77	288	15850	175	123	10	M12x55	145
120	165	60	65	77	346	20750	192	139	12	M12x55	145
130	180	68	74	86	433	28100	193	139	15	M12x60	145
140	190	68	74	86	519	36300	214	157	18	M12x60	145
150	200	68	74	86	519	39000	200	150	18	M12x60	145
160	210	68	74	86	606	48500	219	167	21	M12x60	145
170	225	75	81	95	712	60600	215	162	18	M14x65	230
180	235	75	81	95	712	64100	203	155	18	M14x65	230
190	250	88	94	108	792	75200	178	135	20	M14x75	230
200	260	88	94	108	950	95000	203	156	24	M14x75	230
220	285	98	104	120	990	109000	183	141	18	M16x90	355