

锥套 Taper Bushing




表示方法:

Representation method


SD-25

孔径Bore


型号Bush No



"JA"TD"J"



"M"TD"W"



衬套 Bushing	尺寸(Inches) Dimension							平头螺 钉要求 Cap ScrRews Required	孔径范围 Stock Bore Range			平均 Average
	C	D	L	M	N	E	螺栓分 布圆 Bolt Circle		最小 Minimum	最大 Maximum 标准键槽 Standard Keyway	浅键槽 Shallow Keyway	重量 (约) Weight (Approx)
JA	5/16	2	1	0.20	1.375	11/16	1.656	3-M5×25	3/8	1	11/16	0.9
SH	7/16	211/16	15/16	0.23	1.871	7/8	21/4	3-1/4×13/8	1/2	13/8	11/2	1.0
SDS	7/16	31/8	15/16	0.23	2.187	7/8	211/16	3-1/4×13/8	1/2	15/8	113/16	1.0
SD	7/16	31/8	113/16	0.23	2.187	13/8	211/16	3-1/4×13/8	1/2	15/8	19/16	1.5
SK	9/16	37/8	115/16	0.23	2.812	13/8	35/16	3-5/16×2	1/2	21/8	21/4	2.0
SF	5/8	45/8	21/16	0.23	3.125	17/16	37/8	3-3/8×2	1/2	21/4	27/16	4.0
E	7/8	6	23/4	9/32	3.834	17/8	5	3-1/2×23/4	7/8	27/8	213/16	10.5
F	1	65/8	33/4	11/32	4.437	23/4	55/8	3-9/16×35/8	1	31/4	311/16	15.0
J	11/8	71/4	45/8	5/16	5.148	31/2	61/4	3-5/8×41/2	11/2	313/16	37/8	23.0
M	11/4	9	63/4	11/32	6.494	51/2	77/8	4-3/4×63/4	2	411/16	51/2	55.0
N	11/2	10	81/8	9/16	6.992	85/8	81/2	4-7/8×8	27/16	51/16	51/2	73.0
P+	13/4	113/4	93/8	5/8	8.242	75/8	10	4-1×91/2	215/16	213/16	513/16	120.0
W+	2	15	113/8	11/16	10.437	93/8	123/4	4-11/8×111/2	4	71/2		250.0
S+	31/4	173/4	153/4	3/4	12.125	121/12	156	5-11/4×151/2	6	81/4		400.0